

General Description

The HOV1 is an underported, globe-type, fuel oil valve with a single, quick-opening, stem-guided seat. This 2-way normally closed, bronze safety shutoff valve features a spring-loaded stem which, upon power interruption, drives the teflon seat firmly closed within one second. The HOV1 is available with or without valve seal overtravel interlock (FM proof of closure).

The electrohydraulic actuator consists of a pump applying pressure to a diaphragm attached to the valve stem. Its power unit is immersed in oil and hermetically sealed. The HOV requires no adjustment or service. Stroke is controlled by a travel limit switch and electromagnetic relief valve. The unit rotates 360° for ease of installation. Two-wire connection via 1/2 inch threaded conduit terminal box is standard, and all units are equipped with an auxiliary switch and dust shields.

Specifications

Fluid: Fuel Oil
 No. 2 Fuel Oil at 60 SSU
 No. 4 Fuel Oil at 300 SSU
 No. 5 Fuel Oil at 5000 SSU
 No. 6 Fuel Oil at 5000 SSU (Heated)
 Opening Time: 7-9 seconds
 Closing Time: 1 second max.
 Note: Opening time increases 20% with 50Hz
 Enclosure: Type 1 General Purpose
 Ambient Temperature: -10°F to 125°F (-23° to 52°C)
 Fluid Temperature: 267° max.
 Body/Trim: Bronze, 300# screw
 Seal Material: PTFE
 Port Size: 9/16"

Electrical

Power Requirement: 150 VA
 Standard Voltage: 120V/50-60Hz

Operating Voltage	Amperes		
	Inrush	Opening	Holding
120V/50-60Hz	12.5	1.25	0.09

Auxiliary Switch: One integral SPDT switch, 7.5A@120V, 3.75A@240V, (900VA max.). Switch actuates at energized end of stroke (not adjustable).

Proof of Closure Switch (Valve Seal Overtravel Interlock):
 Optional factory set non-field adjustable SPDT switch, 15A@120V, 7.5A@240V (1800VA max.).



Installation

May be mounted with actuator upright or horizontal with switches uppermost.

Approvals:

UL listed
 FM Approved
 CSA Certified to:
 1) Standard C22.2 No. 139 "Electrically Operated Valves,"
 File 113070.

Specifications

Catalog Number	Pipe Connection (inch NPT)	Cv Flow	Max. Operating Pressure Differential (psi)	Const. Ref.	Opening Time (Sec.)	Shipping Weight lbs.
Standard						
HOV1A302T15	1/2	4	300	1	7-9	12
HOV1A307T15	3/4	5	300	1	7-9	12
HOV1A312T15	1	6	300	2	7-9	13
Valve Seal Overtravel Interlock (FM Proof of Closure)						
HOV1A302T171	1/2	4	300	1	7-9	12
HOV1A307T171	3/4	5	300	1	7-9	12
HOV1A312T171	1	6	300	2	7-9	13

Dimensions: inches

Replacement Actuators:

Standard
HO1A252A15
Models with FM Proof of Closure Valve Seal Overtravel Switch
HO1A252A171

Const. Ref.	A	B	C	D	E
1	3.75	11.56	2.21	3.11	7.55
2	4.25	11.87	2.37	3.42	7.86

